



Features

- ◆ LED Based having long life
- ◆ Available in cutout size 72
- ◆ Available Voltages DC 24V, 30V, 48V, 100/110V, 125V, 200/220V.
- ◆ Confirming to IEC 60974-5-1 & IEC 60947-1
- ◆ Bright Red Vertical & Green Horizontal LED Glow

Applications

Automatic Status Indication of Circuit Breakers,
Isolators and Earth Switches on MIMIC Diagrams of control panels

Head Office.

Plot. No. A/34, Additional Ambarnath MIDC, Anand Nagar, Ambarnath (E), Dist. Thane
Maharashtra, India — 421 506.

Sales Inquiry from outside INDIA : +91-9321252022, +91-251-2621706, 2621518, 2621519 Email:- mimic.ledlamps@gmail.com

Sales Inquiry from INDIA : 09321252022, 0251-2621706, 2621518, 2621519

Website:-www.mimicproducts.com


Quick Contact :- 0 84475 69893

Ordering Code: Name - Mimic Semaphore Indicator 72

Model - SP

Technical Specification

- ◆ Rated Insulation voltage (Ui) :- AC, DC 250V
- ◆ Rated Operational Voltage (Ui) :- DC 240V, 30V, 48V, 100/110V, 125V, 200/220V
- ◆ Voltage Fluctuation Range :- + 15%
- ◆ Rated Operational Current (Ie) :- 11mA max
- ◆ Insulation Resistance :- 1000mΩ over
- ◆ Impulse Withstand Voltage :- +4500V, 3Times For Each Pole(1.2/50μs)
- ◆ Shock Resistance :- 490m/s²
- ◆ Durability :- Over 10000 cycles
- ◆ Degree Of Protection :- Ip52
- ◆ Operating Temperature :- -20 to 60^o c
- ◆ Storage Temperature :- -30 to 75^o c
- ◆ Relative Humidity :- 45 to 85 %
- ◆ Altitude :- Max 2000m
- ◆ Compatible Copper Conductor :- AWG 20 to 14
- ◆ Mounting Plate Thickness :- 1 to 6 mm
- ◆ Confirming to Standard :- IEC 60947-5-1 IEC 60947-1



All dimensions in millimetres

Ordering Requirements

The following code is designed to help in selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box

<u>Ordering code</u>								
MIMIC	-	SP	-	Type of Semaphore	-	Voltage	-	Type of voltage
		Type		Code		voltage		code
MIMIC		22.5mm		22s		24 v	-	24
		30.5mm		30		110 v	-	110
		42mm		42		230 v	-	230
		72mm		72				
Example: Semaphore/30.5mm/230vdc								code: MIMIC-SP- 30 -230 - DC

All specifications, dimensions, weights and tolerances are nominal (typical) and MIMIC reserved the right to vary all data without prior notice. No liability is accepted for any consequence of use.

