

Double Voltmeter

Instrument Division

Data sheet No: DVMI / 10 / 14

DESCRIPTION

Double voltmeters are Moving Iron Instruments. These Instruments are protected from damage or breakage under adverse condition due to its spring loaded jewel & pivot system. And are free from external magnetic field influences because of magnetic shielding & are `CE' certified. These instruments have a very efficient oil damping system, which gives almost a deadbeat movement to the pointer, without irksome oscillation. The movement is light yet sturdy and has a large torque to weight ratio which assures long life to instruments. Readability starts from 10 to 15 degree approximately.



FEATURES

♦ Scale : Non - linear

♦ Scale Colour : Special colour, scales and marks for different ranges . (on request) .

♦ Housing : Engineering plastic.

ELECTRICAL SPECIFICATION

♦ TYPE : Double Voltmeter (Moving Iron)

♦ OPERATING VOLTAGE : 15V to 600V.

100V/110V for PT secondary.

 \Diamond BURDEN (of one Voltmeter): 15V to 30V - <100mA, 50V to 100V -<30mA, 110V to 200V - <15mA,

200V to 600V - < 7.5mA.

 \Diamond FREQUENCY : 45Hz ~ 65Hz. (400Hz. on request)

♦ ACCURACY : Class 1.0% & 1.5%

 \Diamond INSULATION RESISTANCE : Greater then 20M Ω at 500V DC

♦ DIELECTRIC TEST : 2kV RMS for 1 minute.

♦ OVERLOAD CONTINUOUS : 1.2 times
♦ OVERLOAD SHORT TIME : 2 times V_n
♦ OPERATING TEMP. : -10°C to 55°C
♦ STORAGE TEMP. : -20°C to 70°C

♦ CONFORMS TO : I.S. 1248 / I.E.C. 60051 (Part 2) .



MECHANICAL SPECIFICATION

MODEL	DV-SIF-96	DV-SIF-144
SIZE (mm)	96 x 96 x 60	144 x 144 x 50
PANEL CUTOUT (mm)	92 x 92 ^{+0.8}	138 x 138 ^{+1.0}
SCALE LENGTH (Approx.mm)	50	95
WEIGHT (Approx. gms.)	300	600

Ordering information

Type 2) Model 3) Operating Voltage & PTR for Double Voltmeter.



AUTOMATIC ELECTRIC LTD.

Corporate Office :

Rectifier House, 570,

Naigaum Cross Road,

Wadala, Mumbai-400031,India

Email: sales@aelindia.com/ppp@aelindia.com Phone No.: +91-22-24131849/24141794/24162261

Fax No.: +91-22-24112582 Visit us at: http://www.aelindia.com