

LED Semaphore Indicator

SP-RO-72mm

MIMIC LED Semaphore Indicator is used in situations which require visual simulation of the circuit or operating state of a device. Also used for indication of the fault position or ON - OFF positions.

Semaphore Indicator is particularly suitable for monitoring power breakers & disconnectors in complex transformers substations that are represented in form of mimic diagrams of relatively small dimensions.

Applications : Automatic Status Indication of Circuit Breakers, Isolators & Earth Switches. Also for MIMIC Diagrams of control panels.

• Cutout Size : 72 mm

- LED Expected life : 50,000 Hrs.
- Red Vertical & Green Horizontal LED Glow
- IP 52 weather protection.
- Confirming to IEC 60974-5-1 & IEC 60947-1



PERFORMANCE

Rated Insulation Voltage (AC , DC)	250V
Voltage Fluctuation range	+15%
Voltage Rating	20VDC to 32VDC
Rated Operational Current	11 mA
Insulation Resistance (M ohm)	1000
Durability	over 10000 cycles
Shock resistance	490 m / sq. sec
Compatible Copper Conductor	AWG 20 - 14
Impulse Withstand Voltage	+4500V 3 Times for each pole

TECHNICAL

Input Voltage (DC).	24 / 30 / 48 / 100 / 110 / 125 / 200 / 220 / 250 VDC
Cutout Size	72 mm
Operating Temp.	-20deg. to 60 deg. C
Storage Temp.	-30deg. to 75 deg. C
Protection Rating	IP 52
Relative Humidity	45 - 85%
Altitude	Max 2000 m.
Weight	100 gms
Mounting plate thickenss	1 - 6 mm

BODY

Main Body Lens

PBT-Fire Retardent Polycarbonate

Manufactured by : Steam Airetric Controls




Steam Airetric Controls

Plot. No. A/34, Additional Ambernath MIDC, Anand Nagar, Ambernath (E),Dist. Thane Maharashtra, India-421 506.









Plot. No. A/34, Additional Ambernath MIDC, Anand Nagar, Ambernath (E),Dist. Thane Maharashtra, India – 421 506.



٠

•

www.mimicproducts.in