

BEE 1001 CURRENT TRANSFORMER

Beemet current transformers are made of ABS plastic moulding with apertures accepting a wide range of bus bar. These CTs are ultrasonically welded and unbreakable.

GENERAL SPECIFICATIONS

Accuracy Class	0.5, 1 and 1
Primary Current	400A – 4000A
Secondary Current	5A
Frequency	50/60Hz
Rated Load	5VA, 10VA, 15VA, 30VA
Rated Current	2.55 x Ith
Thermal nominal continuous	1.2 times rated current continuously



SALIENT FEATURES

- Compact size with ease of mounting.
- High accuracy and reliability.
- Highly cost effective.

SELECTION CHART

Ratio		1 VA	2.5 VA	5 VA	5 VA
400/5A	Class	0.5	-	-	-
500/5A	Class	0.5	1	-	-
600/5A	Class	0.5	1	-	-
750/5A	Class	-	0.5	1	-
800/5A	Class	-	0.5	1	-
1000/5A	Class	-	0.5	1	-
1200/5A	Class	-	0.5	1	-
1250/5A	Class	-	0.5	1	-
1500/5A	Class	-	0.5	1	-
1600/5A	Class	-	0.5	1	-
2000/5A	Class	-	0.5	1	1
2500/5A	Class	-	0.5	1	1
3000/5A	Class	-	0.5	1	0.5
4000/5A	Class	-	0.5	1	0.5

DIMENSIONS

